

**AURA** is a 37lt-vac created for industrial and professional use with tools. It is provided with a 1400W motor. The automatic start and automatic filter shaker are controlled by the connected tool.



**AURA**

**BL125E BL125A BL125EA**



\*Tool tray and tool not included

Motors	1	1	1
Stage	double	double	double
Volt (V)	220-240	220-240	220-240
Frequency (Hz)	50/60	50/60	50/60
Cooling	by pass	by pass	by pass
P max motor (W)	1400	1400	1400
P max tool (W)	2000	-	2000
Pressure min-max (bar)	-	4-15	4-15
Waterlift (mm H <sub>2</sub> O)	2400	2400	2400
Air flow (m <sup>3</sup> /h)	215	215	215
LpA sonorus 3mt(dB(A))	60	60	60
Total tank capacity (lt)	37	37	37
Weight (Kg)	12,8	12,8	12,8

Also available in M Class



E for electric tool



A for pneumatic tool



EA for electric and pneumatic tools

	1 Flexible hose 3,3mt ø28 complete	<b>ACTF028/3,3/C</b> (standard for BL125E)
	2 Flexible with pneumatic hose ø28 4,5mt	<b>ACTF028P4,5C</b> (standard for BL125A-BL125EA)

	<b>KITV040 (dry kit)</b>	
	3 Crevice tool ø40	<b>ACL P040</b> (optional)
	4 Chrome curved extension wand-male ø40	<b>ACTC038C</b> (optional)
	5 Chrome extension wand ø40	<b>ACTC038D</b> (optional)
	6 Dusting brush ø40	<b>ACPE040</b> (optional)
	7 Nozzle body A/P L400 ø40	<b>ACCS400A/P</b> (optional)
	8 Slide-on brush for floor nozzle L400	<b>ACIP400</b> (optional)
	9 Complete flexible hose mt.2,5 ø40	<b>ACTF038/2,5/C</b> (optional)

	<b>Filters and accessories</b>	
	10 Conic cartridge H14 filter ø202 - H153	<b>FI202153HPL</b> (standard)
	11 Tool tray 40x50cm	<b>CMPU4050</b> (optional)
	12 Polyester filter with ring ø340	<b>FA034P</b> (optional)
	13 Nylon filter	<b>FINY334AT</b> (optional)
	14 Reinforced paper bag 37lt	<b>FI006C</b> (standard)